

Chipping Hammers **GV5 DP**



- **POWERFUL**
- **STRONG**
- **EFFICIENT**

This hammer is the reference on the market and is also very good for roughening work. It is sold with closed screwed retainer

TECHNICAL DATA	GV5D
Weight (kg)	5.2
Length (mm)	410
Shank size (mm)	H19X50 Con23/16x70 d/H17.3x60
Nominal pressure (bar)	5.5
Bore(mm)	28
Piston stroke (mm)	61
Blows/min (l/min)	2550
Air consumption (l/min)	573
Ø hose (mm)	13
Sound level db (A) with muffler (LWAG)	103
Level of vibration (m/s²): Norm ISO 5349	8.7
Level of vibration (m/s²): Norm ISO 28927-10 standard. New method of measurement (second hand on the cylinder)	9.9

Recommended for :
- Preparation of the walls before facades works to hang on products
- Facades : <ul style="list-style-type: none"> - cleaning and repairing of the joints of bricks and stones - removing plaster, tiling, roughcast - removing tiling on the floor and on the walls
- Other works linked to buildings : <ul style="list-style-type: none"> - Roughening - Installation of electric caskets - Cleaning residues of cement, concrete, cofferings
- Small demolition (cement, tiles, renderings, coatings)

TOOLS

TOOLS	Shank	Total Length (mm)	Width	Code
Chisel	H19X50	300		2200
		500		2201
Flat chisel		300		2202
		500		2203
Hose d. 13 mm		500		15053

Chisel and flat chisel**Hose**